

MONITOR P/N: STSM207

Screen Size (Diagonal)	7"
Screen Ratio	16:9
Contrast Ratio	300:1
Video System	NTSC
Voltage Input	12~24 Vdc
Operating Temperature °F (C°)	15° to 140° (-10° to +60°)
Storage Temperature °F (C°)	-5° to 160° (-20° to +70°)
Dust/Water Rating	IP67
Shock Rating	100g
Vibration Rating	15g
Speaker Impedance	8 Ohms
Weight lb.	1.5
Dimensions WxHxD inches	7" x 5.75" x 1"
Sun Shade	Included
Brightness	500 cd/m2



Optional Cameras:

STSC117



Vertical Tilt - Camera
(camera lens automatically pivots up/down w/ trigger inputs)

STSC127



Shutter Camera
(camera lens is protected by automatic lens cover)

CAMERA P/N: STSC107

Image Device	1/3" CCD
Pixels	250,000
TV Lines	380
Infrared LED's	6 High-Output
Dust/Water Rating	IP67
Field of View	120°
Operating Temperature °F (C°)	5° to 150° (-15° to +65°)
Storage Temperature °F (C°)	-5° to 160° (-20° to +70°)
Audio	Yes
Heater	Thermostat Controlled
Shock Rating	100g
Vibration Rating	10g
Weight lb.	.5
Dimensions WxHxD inches	2.5" x 1.7" x 2.5"
Construction	Cast Aluminum Housing w/ Stainless Steel Mounting Bracket & Weather Shield

Standard Camera Included w/ Kit:

STSC107



HARNESS P/N: STSH307

60' Heavy Duty with Twist-lock Connectors



VisionSystems



A Century of Automotive Vision Safety

90-21 144th Place
Jamaica, New York 11435
Phone: 718-526-2601
Fax: 718-297-0323
www.roscovision.com
Cat No. 0109