

MONITOR P/N: STS7CLR/MTR

| | |
|-------------------------------|----------------------------------|
| Screen Size (Diagonal) | 7" |
| Resolution (NTSC) | 1440(H) X 234(V) |
| Voltage Input | 12~32 Vdc |
| Contrast Ratio | 550:1 |
| Power Consumption | Max 9.6W |
| Viewing Angles Up/Dn/Lt/Rt | 55 x 55 x 75 x 75 |
| Maximum No. of Cameras | 3 |
| Selectable Mirror/Normal | Yes |
| Operating Temperature F° (C°) | -22° to +176° (-30° to +80°) |
| Dimension WxHxD inches (mm) | 7.7 x 5.7 x 1.3 (195 x 145 x 33) |
| Weight lb. (Kg) | 1.1 (0.5) |



MOTORIZED REAR CAMERA P/N: STSCLR/MTRCAM

| | |
|-------------------------------|-----------------------------------|
| Image Device | Sony® Color 1/3" CCD |
| Effect Pixels (NTSC) | 512 x 492 |
| Horizontal Resolution | 380 lines |
| Field of View; Diagonal | 110° |
| Video Output | 1.0 Vp-p, 75 Ohm |
| Lens Focal Length | 2.4 mm |
| Sync System | Internal |
| Minimum Illumination | 1.0 LUX |
| Infrared LED Elements | 8 |
| Night Vision Range | 16 feet |
| Power Supply | 12 Vdc from Monitor |
| Operating Temperature F° (C°) | -22° to +176° (-30° to +80°) |
| Weight lb. (Kg) | 0.83 (0.38) |
| Dimensions WxHxD inch (mm) | 3.66 x 2.76 x 2.79 (93 x 70 x 71) |

SIDE CAMERA P/N: STSCLR/SDELCAM

STSCLR/SDERCAM


| | |
|-------------------------------|----------------------------------|
| Image Device | Sony® Color 1/3" CCD |
| Effect Pixels (NTSC) | 512 x 492 |
| Horizontal Resolution | 380 lines |
| Field of View; Diagonal | 110° |
| Lens Focal Length | 2.4 mm |
| Minimum Illumination | 1.0 LUX |
| Infrared LED Elements | 8 |
| Night Vision Range | 16 feet |
| Power Supply | 12 Vdc from Monitor |
| Operating Temperature F° (C°) | -22° to +176° (-30° to +80°) |
| Weight lb. (Kg) | 0.77 (0.35) |
| Dimensions WxHxD inch (mm) | 2.77 x 2.65 x 4.9 (70 x 67 x 24) |

HARNESS P/N:

| | |
|---|----------------|
| 60' Heavy Duty with Twist-lock Connectors | STS/HAR6P60/MF |
| 25' Heavy Duty with Twist-lock Connectors | STS/HAR4P25/MF |

KIT P/N: STS7CLR/3CKIT

Monitor, Motorized Rear Camera, 2 Side Cameras, Power/Distribution Cable, 60' Harness, Two 25' Harnesses, Mounting Hardware, Sunshade & Installation/ User Manual



A Century of Automotive Safety

90-21 144th Place
Jamaica, New York 11435
Phone: 718-526-2601
Fax: 718-297-0323
www.roscomirrors.com

Vision Systems



CAT NO. 707209