

Heavy Duty Color Backup Camera System With 5" LCD Monitor & Two Camera Inputs

for Work Trucks, Vans, Buses, RV's & Trailers









- Rugged High Resolution 5" LCD Color Monitor With Ultra Sharp Display
- System Can Accept Up to 2 Camera Inputs for Multiple Camera Views
- Weatherproof Heavy Duty Camera Provides 120° Field Of Vision
- 18 InfraRed LED's in Camera Provide Up To 30 Ft. of Night Time Visibility
- Built In Camera Microphone & Powerful Monitor Speakers
- Versatile Mounting On Dashboard or Overhead Location
- One Year Warranty Included





MONITOR P/N: STSM208 (Included In Kit)

Screen Size (Diagonal)

Maximum No. of Cameras 2 Inputs/Channels

Screen Ratio 16:9 Contrast Ratio 500:1 **NTSC** Video System Voltage Input 12 ~ 32 Vdc

Operating Temperature °F (C°) 5° to 149° (-15° to +65°) Storage Temperature °F (C°) -4° to 158° (-20° to +70°)

Vibration Rating 6.9G @ 10-30Hz, 3mm Amplitude

Speaker Impedance 8 Ohms Weight 0.7 lb.

Dimensions W x H x D 5.5" x 4" x 1.1"

Other Features Auto dimming backlit buttons

Mounting Brackets Standard Duckfoot, Optional U-Bracket

& AMPs Mount



Optional U-Bracket

CAMERA P/N: STSC141 (Included In Kit)

Sony 1/4" CCD **Image Device Pixels** 270,000 TV Lines 420

InfraRed LED's

18 High-Output

0 LUX (Infrared LED's on) Minimum Illumination

Night Vision Range 30 Feet

Video Output 1.0 Vp-p, 75 Ohm

Dust\Water Rating IP69k **Shock Rating** 100G Vibration Rating 15G Field of View 120°

Operating Temperature °F (°C) -15° to 160° (-25° to +70°) Storage Temperature °F (°C) -20° to 176° (-30° to +80°)

Weight

3" x 2" x 2" Dimensions W x H x D



Standard Camera



STSC106 Wide Angle Bullet Camera



STSC109B Universal L/R Side Camera



STSC112 License Plate Camera

HARNESS P/N: STSH303 (Included In Kit)

33' Harness

Optional Harnesses:

STSH304 - 16.5' Harness Extension STSH341 - 65' Heavy Duty w/ Twist -

Lock Connectors

STSH394 - Heavy Duty Coil Cord Quick Disconnect Kit w/ 16.5' Harness

STSH303 Standard Harness



