

Heated Backup Camera System With Color 7" WATERPROOF Multi-View LCD Monitor

for Open & Harsh Cab Environments









KIT P/N: STSK7360



- 7" Waterproof Monitor With Membrane Touchpad
- High Resolution With Ultra Sharp DIGITAL Display & LED-Backlit Panel
- Multi-View LCD Monitor Can Accept Up To 4 Camera Inputs
- Heavy Duty, Heated Camera Provides 120° Field Of Vision
- 6 InfraRed LEDs in Camera Provide Up To 30 Ft. of Night Time Visibility
- Integrated Audio Built-In Camera Mic & Powerful Monitor Speakers
- Versatile Mounting On Dashboard or Overhead Location
- Two Year Warranty Included





MULTI-VIEW WATERPROOF MONITOR P/N: STSM207 (Included In Kit)

Screen Size (Diagonal)

Maximum No. of Cameras 4 Inputs/Channels

16:9 Screen Ratio Contrast Ratio 300:1 Video System **NTSC** 12~24 Vdc Voltage Input

Operating Temperature °F (C°) -22° to 158° (-30° to $+70^{\circ}$) Storage Temperature °F (C°) -40° to 176° (-40° to +80°)

Dust\Water Rating **IP67 Shock Rating** 100a Vibration Rating 8g Speaker Impedance 8 Ohms Weight 1.7 lb

7" x 5.75" x 1" Dimensions W x H x D Sun Shade Included **Brightness** 400 cd/m2

Monitor Mounting Options Versatile Duckfoot & U-Bracket



HEATED CAMERA P/N: STSC107 (Included In Kit)

1/3" CCD **Image Device Pixels** 250.000 TV Lines 380

InfraRed LED's 6 High-Output

Dust\Water Rating IP67 120° Field of View

Operating Temperature °F (°C) -22° to 158° (-30° to $+70^{\circ}$) Storage Temperature °F (°C) -40° to 176° (-40° to +80°)

Audio

Thermostat Controlled Heater

Shock Rating 100a Vibration Rating 10g Weight 0.88 lbs.

Dimensions W x H x D 2.7" x 1.7" x 2.2"

Construction Cast Aluminum Housing w/

Stainless Steel Mounting Bracket & Weather Shield



STSC107 Standard Camera (included in kit)



Vertical Tilt Camera (camera lens automatically pivots up/down w/ trigger inputs)

Optional Cameras:



Shutter Camera (camera lens is protected by automatic lens cover)



STSC128 Side Mount Camera (universal left or right side mount camera)

HARNESS P/N: STSH307 (Included In Kit)

60' Heavy Duty w/ Twist - Lock Connectors

Optional Harnesses:

STSH308 - 16.5' Harness

STSH310 - 60' Harness Extension (used with STSH308)

STSH306 - 60' Harness (for STSC117 Only)



STSH307 Standard Harness

Optional Harnesses:



STSH308



STSH310



STSH306



