



STSK7565

# Heavy Duty Color Backup Camera System With 7" LCD Monitor & Two Camera Inputs

for Work Trucks, Vans & Buses



KIT P/N: STSK7565

- High Resolution 7" LCD Color Monitor With Rugged Housing
- Membrane Touch Pad With Illuminated Buttons
- System Can Accept Up to 2 Camera Inputs for Multiple Camera Views
- Weatherproof Heavy Duty Camera Provides 120° Field Of Vision
- 18 InfraRed LED's in Camera Provide Up To 30 Ft. of Night Time Visibility
- Built In Camera Microphone & Powerful Monitor Speakers
- Versatile Mounting On Dashboard or Overhead Location
- One Year Warranty Included

### MONITOR P/N: STSM254 (Included In Kit)

Screen Size (Diagonal)	7"
Maximum No. of Cameras	2 Input/Channel
Screen Ratio	16:9
Contrast Ratio	500:1
Video System	NTSC
Voltage Input	12 ~ 32 Vdc
Operating Temperature °F (C°)	-5° to 149° (-20° to +65°)
Storage Temperature °F (C°)	-4° to 158° (-20° to +70°)
Dust/Water Rating	IP67
Shock Rating	100g
Vibration Rating	6g
Speaker Impedance	8 Ohms
Weight	0.9 lb.
Dimensions W x H x D	5.7" x 4.9" x 1"
Other Features	Auto dimming backlit buttons
Mounting Brackets	Standard Duckfoot, Optional U-Bracket & AMPs Mount



Optional U-Bracket Mount

### CAMERA P/N: STSC150 (Included In Kit)

Image Device	1/4" CMOS
Pixels	250,000
TV Lines	420
InfraRed LED's	18 High-Output
Minimum Illumination	0 LUX (InfraRed LED's on)
Night Vision Range	30 Feet
Video Output	1.0 Vp-p, 75 Ohm
Dust/Water Rating	IP69k
Shock Rating	100G
Vibration Rating	8G
Field of View	120°
Operating Temperature °F (C°)	-5° to 158° (-20° to +70°)
Storage Temperature °F (C°)	-40° to 176° (-40° to +80°)
Weight	.6 lb.
Dimensions W x H x D	3.74" x 2.76" x 3.39"



STSC150 Standard Camera

#### Optional Cameras:



STSC153 Heated Shutter Camera (camera lens is protected by automatic lens cover)



STSC112 License Plate Camera

STSC106 Wide Angle Bullet Camera

STSC152 Heated Backup Camera

STSC109B Universal L/R Side Camera

### HARNESS P/N: STSH320 (Included In Kit)

65' Heavy Duty w/ Waterproof Twist - Lock Connectors

#### Optional Harnesses:

- STSH321 - 16.5' Harness
- STSH322 - 33' Harness
- STSH323 - 1' Conversion Harness From 6 Pin to 4 Pin (for STSC109B, STSC106, STSC112 Only)

#### Six Pin Connectors



STSH320 Standard Harness

#### Optional Harnesses:



STSH321

STSH322



STSH323