



STSK4533

# MOR-Vision™ Helps to Confirm Safe Reverse Operations With Simple Replacement of OEM Rearview Mirror

Rearview Mirror/Monitor Combo Backup Camera System



Monitor P/N: STSM230



Camera P/N: STSC112

Ideal for all small to medium size vehicle applications.



Minivan



Type A Bus



Cargo Van



Work Truck

## MOR-VISION

- Mirror Monitor Allows the Driver to See The Camera Image Behind The Vehicle When in Reverse
- Normal Mirror View Reappears Once Vehicle is Shifted Into All Other Modes of Vehicle Operation
- Superb Night Vision
- 4.3" LCD Color Monitor in Rearview Mirror
- Simple Rearview Mirror Install
- On Screen Menu
- 2 Camera Input Capability
- Automatic Triggers for Cameras
- 150° Diagonal Field Of Vision
- Complies with RIN 2127-AK43.
- 1 Year Warranty



90-21 144th Place, Jamaica, New York 11435  
TEL (800) 227-2095 • FAX (718) 297-0323  
info@roscomirrors.com  
www.roscovision.com www.roscomirrors.com





According to data from a recent study by the National Highway Traffic Safety Administration, shifting into reverse may be **more** dangerous than previously thought. According to the first study conducted on the issue, 463 people were killed by vehicles backing up in 2007. That is more than 8 deaths per week. In the same period, about 48,000 people were injured in backup accidents. Rosco Vision Systems video technology now makes it affordable for drivers to have an added dimension of safety. A Rosco backup camera makes backing up easier and your fleet or personal vehicle less prone to accidents!



**Monitor P/N: STSM230**



**Camera P/N: STSC112 (Included)**

## KIT P/N STSK4533

### Monitor P/N: STSM230

Screen Size Diagonal	4.3
Resolution (Pixels)	480 x 272
Screen Ratio	16:9
Power Supply	12 Vdc
Max. No Cameras	2
Shock Rating	100g
Vibration Rating	15g
Working Temp. F° (C°)	-5° to +140° (-20° to +60°)

### Camera P/N: STSC112

Pixels	512 X 582
Resolution (Diagonal)	420
Illumination	0.1 Lux
Waterproof Grade	IP69K
Nominal Voltage	12 Vdc
Working Temp. F° (C°)	68° to +158° (-20° to +70°)

### Harness P/N: STSH330

26' Harness

The camera has an advanced CMOS lens sensor able to process excellent images in all light conditions, even in complete darkness. The camera also has a 170° diagonal field of vision for superb coverage behind the vehicle, and complies with the latest NHTSA 49 CFR Parts 571 & 585 (RIN 2127-AK43).

### Optional Cameras (Not Included):



P/N: STSC141



P/N: STSC106



P/N: STSC130B

### Optional Harnesses:

(Necessary when using STSC141 & STSC106)

STSH373 - Adapter for RCA connector to 4-pin din

STSH374 - Adapter for 12V power source



90-21 144th Place, Jamaica, New York 11435  
 TEL (800) 227-2095 • FAX (718) 297-0323  
 info@roscomirrors.com  
 www.roscovision.com www.roscomirrors.com

